PRODUCT CARD

ISKV E2

2-GLAZED TOP-HUNG WOODEN ROOF WINDOW

INTENDED USE

in roofs with a pitch of 15°-65°

window designed for communication in residential and commercial locations

MATERIAL

pine wood impregnated and painted with colourless eco-friendly varnish

FEATURES

- 2-glazed package
- door handle with two keys as standard
- ventilation option thanks to the micro-opening function in the handle
- exceptional tightness thanks to four seals
- NEO-VENT air vent enabling fresh air supply
- two sash opening functions: tilt and slide
- the possibility of freely accessing the roof
- convenient cleaning thanks to the sliding function - the outer side of the sash (glass) is directed inwards
- can be fitted with additional sealing accessories (AKP, UTB)

WINDOW PANE	
construction E2	4H/16/4T
window package	24 mm
low-emission coating	■
gas	argon
internal laminated glass	–
external tempered glass	■
warm spacer bar	■
heat transfer coefficient of glass	Ug = 1,0 W/m²K
WINDOW	
window heat transfer coefficient	Uw = 1,3 W/m²K
water resistance	E1050
air permeability	Class 4
wind load resistance	Class C3
acoustic properties	Rw = 32 dB
impact resistance	Class 3
COLOUR	
wood	natural
cladding	anthracite RAL 7016

AVAILABLE DIMENSIONS															
glazing area [m²]	0,20	0,27	0,36	0,45	0,55	0,45	0,56	0,70	0,81	0,71	0,89	1,04	0,91	1,12	0,88
size symbol	01	02	03	04	15	05	06	07	13	08	09	14	10	11	12
window size: width × height [cm]	55×78	55×98	66×98	66×118	66×140	78×98	78×118	78×140	78×160	94×118	94×140	94×160	114×118	114×140	134×98
ISKV E2		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	