



PRODUCT CARD

ISWX E2

2-GLAZED ROOF WINDOW WOODEN



INTENDED USE

in roofs with a pitch of 15°-65°

window designed for communication in residential and commercial locations

recommended for unheated attics

MATERIAL

pine wood impregnated and painted with colourless eco-friendly varnish

FEATURES

- 2-glazed package
- excellent thermal insulation
- door handle with two keys as standard
- ventilation option thanks to the micro-opening function in the handle
- exceptional tightness thanks to four seals
- enables safe access to the roof
- the pivot point at the top of the sash allows it to open up to 180°
- smooth opening of the sash within a range of up to 30°
- can be installed with additional sealing accessories (AKP, UTB)

WINDOW PANE

construction E2	4H/16/4T
window package	24 mm
low-emission coating	■
gas	argon
internal laminated glass	-
external tempered glass	■
warm spacer bar	■
heat transfer coefficient of glass	U _g = 1,0 W/m ² K

WINDOW

window heat transfer coefficient	U _w = 1,2 W/m ² K
water resistance	E1050
air permeability	Class 4
wind load resistance	Class C3
acoustic properties	R _w = 32 dB
impact resistance	Class 3
load capacity of safety devices	350N

COLOUR

wood	natural
cladding	anthracite RAL 7016

AVAILABLE DIMENSIONS	
glazing area [m ²]	0,21
window size: width x height [cm]	55x78
ISWX E2	✓