



Section A-A
1:5

Window height

20 mm
80 mm

60-150 mm
25 mm

Section B-B
1:5

Window width 30-60 mm

20-30 mm

- ① Tiles 120 mm
- ② VELUX flashing (EDW 15°-90°)
- ③ VELUX window (GGL 15°-90°)
- ④ VELUX underfelt collar (BFX)
- ⑤ VELUX insulation frame (BDX)
- ⑥ VELUX vapour barrier collar (BBX)
- ⑦ Gasket on BBX in window rebate
- ⑧ VELUX vapour barrier tape (BBX)
- ⑨ VELUX lining (LS-)
- ⑩ Existing rafter
- ⑪ Trimmer where necessary (Non-VELUX)
- ⑫ Underfelt/Breather membrane (Non-VELUX)
- ⑬ Installation batten (Non-VELUX)

Size	Width	Size	Height
CK--	550	-K25	550
FK--	660	-K27	624
MK--	780	-K02	778
PK--	942	-K04	978
SK--	1140	-K06	1178
UK--	1340	-K08	1398
		-K10	1600
		-K12	1800

© VELUX GROUP

® VELUX, VELUX logo are registered trademarks

VELUX®

File name:
Single_GGL_3_Tiles120_LS_EN1

Drawing no.: 1668EN3 SCo ---

Create date 2024-10-25	Rev. date -	Format A3	Scale 1:5
---------------------------	----------------	--------------	--------------

Note: When installing VELUX Roof Windows, flashings and installation products, the manufacturers instructions and current building and fire regulations, where applicable, must be met.