



Section A-A
1:5

60-150 mm
25 mm

Window height

20 mm
80 mm

Section B-B
1:5

Window width 30-60 mm

20-30 mm

- ① Tiles 120 mm
- ② VELUX flashing (EDW 15°-90°)
- ③ VELUX window (GPU 15°-55° (75°))
- ④ VELUX underfelt collar (BFX)
- ⑤ VELUX insulation frame (BDX)
- ⑥ VELUX vapour barrier collar (BBX)
- ⑦ Gasket on BBX in window rebate
- ⑧ VELUX vapour barrier tape (BBX)
- ⑨ VELUX lining (LS-)
- ⑩ Existing rafter
- ⑪ Trimmer where necessary (Non-VELUX)
- ⑫ Underfelt/Breather membrane (Non-VELUX)
- ⑬ Installation batten (Non-VELUX)

Size	Width	Size	Height
CK--	550	-K04	978
FK--	660	-K06	1178
MK--	780	-K08	1398
PK--	942	-K10	1600
SK--	1140		
UK--	1340		

© VELUX GROUP ® VELUX, VELUX logo are registered trademarks

VELUX®			
File name: Single_GPU_3_Tiles120_LS_EN1			
Drawing no.:	655EN3	SCo	---
Create date	Rev. date	Format	Scale
2024-12-16	-	A3	1:5

Note: When installing VELUX Roof Windows, flashings and installation products, the manufacturers instructions and current building and fire regulations, where applicable, must be met.